

SAFETY DATA SHEET

Version 2 Revision Date 04/07/2016
Printed 04/12/2016

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name: Cemented Tungsten Carbide Cutting Tools and other Products with Cobalt/Nickel/Chrome Binders. 10% Co < 25%

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Cutting tools, End Mills, Slitting Saws, Drill Bits, Drill Rod, Wear Parts, Tools, Reamers

1.3 Details of the supplier of the safety data sheet

Company: ROBBJACK CORPORATION
3300 NICOLAUS ROAD
LINCOLN CA. 95648

Telephone: 1-916-645-6045
Fax: 1-916-645-0146
E-mails: ken@robbjack.com
bill@robbjack.com

1.4 Emergency telephone number

Emergency Phone # 1-800-222-1222

2. HAZARDS IDENTIFICATION

As sold, solid hard metal blanks do not present inhalation, ingestion or other chemical hazards. However, operations such as grinding, cutting, burning and welding of such products may release **HARDMETAL IN THE FORM OF DUSTS OR FUMES**, which may present health hazards. The health hazards described below relate to only those operations that release hard metal and its individual components, such as tungsten carbide and cobalt dusts or fumes.

2.1 Classification of the substance or mixture

Classification according to 29 CFR 1910.1200:

Acute Tox. 3, H331; Carc. 1B, H350i; STOT RE 1, H372; Eye Irrit. 2B; H320; Repr. 2, H361f; Resp. Sens. 1B, H334; Skin Sens.1, H317; Aquatic Acute 1, H400; Aquatic Chronic 2, H411

2.2 GHS Label elements, including precautionary statements

Hazard pictogram(s):



Signal word:

Danger

Hazard Statement(s):

Toxic if inhaled (H331); May cause cancer by inhalation (H350i); Causes damage to lungs through prolonged or; repeated exposure by inhalation (H372); Causes eye irritation (H320); Suspected of damaging fertility (H361f); May cause allergy or asthma symptoms or; breathing difficulties if inhaled (H334); May cause an allergic skin reaction (H317); Very toxic to aquatic life with long lasting effects (H410)

Precautionary statement(s):

Do not breathe dust (P260); Wear protective gloves and protective clothing. (P280); In case of inadequate ventilation wear respiratory protection (P285); Avoid release to the environment (P273); IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician (P304 + P341 + P342 + P311) If eye irritation persists: If skin irritation or rash occurs: Get medical advice/attention (P337 + P333+ P313)

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

PBT or vPvB: Tungsten carbide and cobalt are inorganic substances and therefore, the PBT and vPvB assessment is not required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance Name: Tungsten Carbide

EINECS Number: 235-123-0

CAS Number: 12070-12-1

Concentration range, % by weight: >50% Cermets grades: 10-20%

Classification GHS: Tungsten carbide is not classified under GHS

Substance Name: Cobalt, Powder (>99% <1mm) (Respirable fraction=0,01%w/w)

EINECS Number: 31-158-0

CAS Number: 7440-48-4

Concentration range, % by weight: 10% = cobalt concentration < 25 %

Classification GHS: Carc. 1B, H350i; Eye Irrit. 2B, H320; Repr. 2; H361f; Acute Tox. 1, H330; Acute Tox. 4, H302; Resp. Sens. 1B, H334; Skin Sens. 1, H317; Aquatic Acute 1 (M=10), H400; Aquatic Chronic 1, (M=1), H410

4. FIRST AID MEASURES

4.1 Description of first aid measures:

Eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing

Inhalation: Remove to fresh air. Seek medical attention if required.

Ingestion: Rinse mouth with water and drink plenty of water afterwards. Seek medical advice if required. Never give anything by mouth to an unconscious person.

Skin: Remove contaminated clothing. Immediately wash with soap and water and rinse thoroughly. Seek medical attention if required.

General advice: After first aid, get appropriate medical attention.

4.2 Most important symptoms and effects, both acute and delayed:

In general, metal powders or dust may cause mechanical eye and skin irritation. Inhalation of powder or dust may cause mild respiratory tract irritation. Chronic

inhalation of hard metal powder/dust has the potential for causing transient or permanent respiratory disease, including occupational asthma and interstitial lung fibrosis. Hard metal powders may cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed: None known

5. FIREFIGHTING MEASURES

- 5.1 Extinguishing media:** Mixture is non-flammable. Extinguishing methods depend upon hazards in vicinity. Use water or dry extinguishing powders, sand, CO or other inert material as extinguishing media. Do not use water if any water-reactive metal powders are nearby.
- 5.2 Special hazards arising from the substance or mixture:** Under rare favoring conditions of particle size, dispersion, concentration, and strong ignition source, tungsten carbide and cobalt powders or dusts may present a fire or explosion hazard.
- 5.3 Advice for firefighters:** Use a self-contained breathing apparatus and a protective suit.
- 5.4 Further information:** No data available

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures:** Avoid contact with skin and eyes, and formation and accumulation of dust. Use personal protective equipment (i.e. gloves, safety goggles, dust respirator) as specified in Section 8 of this SDS. Ventilate area of spill.
- 6.2 Environmental precautions:** Avoid release into the environment.
- 6.3 Methods and materials for containment and cleaning up:** Use clean-up methods which avoid dust generation, such as vacuuming (with filter that prevents re-suspension of dust) or wet clean-up, and fill into appropriate sealable containers. Clean remaining spills with water. Recycle or dispose of wastes according to regulations. See section 13.1 below.
- 6.4 Reference to other sections:** See sections 8 and 13 for exposure controls and disposal considerations.

7. HANDLING AND STORAGE

- 7.1 Precautions for safe handling:** Ensure adequate ventilation and, if necessary, exhaust ventilation when handling or transferring this material. Use good housekeeping procedures to prevent accumulation of dust and ensure that accepted limit values are complied with. Wear personal protective equipment when handling.
- 7.2 Conditions for safe storage, including any incompatibilities:** Store in a tightly closed supplied container in a well ventilated area. Store under dry and cool conditions and away from incompatible materials (acids and oxidizing agents) and direct sunlight.
- 7.3 Specific end use(s):** Production of sintered hard metal articles (e.g. cutting and machining tools, mining and drilling tools, wear parts).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters:**

Country	For tungsten and insoluble compounds, as tungsten		Cobalt	
	8-h Limit Value (mg/m ³)	Short-term Limit Value (mg/m ³)	8-h Limit Value (mg/m ³)	Short-term Limit Value (mg/m ³)
ACGIH TLV	5	-	0.02	-
Austria	5*	10*	0.1	0.4
Belgium	5	10	0.02	-
Canada (Québec)	5	10	0.02	-
Denmark	5	10	0.01	0.02
Hungary	-	-	0.1	0.4
Poland	5	-	-	-
Spain	5	10	0.02	-
Sweden	5	-	0.02	-
Switzerland	5*	-	0.05*	-
USA - NIOSH	5	10 ¹	0.05	-
USA - OSHA	-	-	0.1	-
United Kingdom	5	10	0.1*	-

* Inhalable aerosol; ¹15-minutes

DNELs and PNECs

Exposure pattern	Route	DNEL	
		Tungsten Carbide	Cobalt
Short-term-systemic effects	Dermal	Not applicable	Not derived because cobalt dermal absorption is negligible
Short-term-systemic effects	Inhalation	Not applicable	Long-term DNEL is expected to be adequately protective of acute exposure
Short-term-systemic effects	Oral	Not applicable	Not applicable
Short-term-local effects	Dermal	Not applicable	No DNEL derived, because substance is classified as skin sensitizer with no dose-response relationship available.
Short-term-local effects	Inhalation	Not applicable	Long-term DNEL is expected to be adequately protective of acute exposure
Long-term - systemic effects	Dermal	- Workers: 1.8 mg/kg bw/day (1.7 mg W/kg/day) - General Population: 0.51 mg/kg bw/day (0.48 mg W/kg/day)	Limited data exist for DNEL development
Long-term - systemic effects	Inhalation	- Workers: 6.2 mg/m ³ (5.8 mg W/m ³) - General Population: 1.8 mg/m ³ (1.7 mg W/m ³)	- Workers: 0.040 mg/m ³ - General population: 6.3 µg/m ³
Long-term-systemic effects	Oral	- Workers: Not applicable - General Population: 0.51 mg/kg bw/day (0.48 mg W/kg/day)	- Workers: Not applicable - General Population: 0.0095 mg/kg bw/day
Long-term-local	Dermal	Not applicable	No DNEL derived, because

effects			substance is classified as skin sensitizer with no dose-response relationship available
Long-term-local effects	Inhalation	Not applicable	- Workers: 0.040 mg/m ³ - General Population: 0.0063 mg/m ³

The most relevant routes of potential exposure to workers would be the dermal and inhalation routes. The relevant routes of exposure for the general population are the oral, dermal, and inhalation routes. Based on the available acute toxicity data (oral, dermal, inhalation), tungsten carbide is not an acute toxicant. Therefore, derivation of DNEL_{long-term} will be sufficient to control potential risks associated with short-term exposures. In addition, tungsten carbide was not irritating to either the eyes or skin and was not sensitizing to the skin in standard tests. Therefore, tungsten carbide does not appear to elicit local toxicity effects and deriving a DNEL for local effects is not necessary.

Cobalt is a skin sensitizer and a DNEL was not derived because no dose-response relationship was available.

PNEC	Value	
	Tungsten	Cobalt
PNEC aqua – freshwater	0.338 mg dissolved tungsten/L	0.00051mg dissolved cobalt/L
PNEC aqua - marine water	0.0338 mg dissolved tungsten/L	0.00236 mg dissolved cobalt/L
PNEC aqua – intermittent releases	0.310 mg dissolved tungsten/L	Not applicable
PNEC sediment freshwater	960 mg tungsten/kg	11,2 mg cobalt/kg dry wt 9.5 mg cobalt/kg dry wt (added Risk Approach)
PNEC sediment marine	96 mg tungsten/kg	9.5 mg cobalt/kg dry wt
PNEC soil	2.17 mg tungsten/kg dry soil	10.9 mg cobalt/kg dry soil
PNEC sewage treatment plant	9.39 mg tungsten/L	0.00037 mg cobalt/L
PNEC oral (secondary poisoning)	11 mg tungsten/kg food	Not potential for bioaccumulation

8.2 Exposure controls: Appropriate engineering controls, Engineering controls may include local ventilation systems with dust filters depending on degree of process automation and containment (e.g. closed vs. open processes).

Personal protective equipment:

Eye/face protection

Use of safety glasses as appropriate and reasonably necessary, depending on degree of process automation and containment (e.g. closed vs. open processes).

Skin protection

Use of work gloves (For hard metal: impervious gloves. For PEG-residues: butyl rubber and nitrile rubber) and work clothes as appropriate and reasonably necessary, depending on degree of process automation and containment (e.g. closed vs. open processes).

Respiratory protection

Use of respiratory protection as appropriate (P-Series for particles, A-series for possible PEG residues) and reasonably necessary, depending on degree of process automation and containment (e.g. closed vs. open processes).

Environmental exposure controls:

Air Emission Controls

Environmental controls for air (present in >90% of the sites²):

- Fabric or bag filters (reported most common)
- Wet scrubbers (reported second most common)
- Ceramic filters
- Dry or semi-dry scrubbers
- Electrostatic precipitation (not common)

Water Emission Controls

The 50th percentile or reported site-specific removal efficiency for nine sites.

Environmental controls for water (present in >90% of the sites for metal compound production²):

- Chemical precipitation
- Sedimentation
- Filtration
- Electrolysis (not common)

1 Typical environmental controls are provided for illustrative purposes and should be applied as appropriate and reasonably necessary to prevent adverse effects, indicated by a risk characterization ratio (RCR) of less than one, on human health and the environment.

2 Based on input parameters derived from the Specific Emission Release Categories (spERCs) for metals (ARCHE, 2010), spERC for Manufacture and Recycling of Massive Metal and Metal Powder v.1.2.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

• Appearance	Black or grey powder
• Odor	Odorless
• Odor threshold	Not applicable as substances are odorless
• pH	Not relevant due to physical form (powder)
• Melting point/freezing point	2785-2920 °C (WC) 1494 °C (Co)
• Initial boiling point/boiling range	6000 °C (WC) 2927 °C at 101.325 kPa (Co)
• Flash point	Not relevant as the substances are inorganic
• Evaporation rate	Not relevant due to physical form (powder)
• Flammability	Non-Flammable
• Upper/lower flammability or explosive limits	Not relevant as the substances are not flammable
• Vapor pressure	Not relevant due to physical form
• Vapor density	Not relevant due to physical form
• Relative density	15.63 - 15.7 g/cm ³ (WC) 8.89 g/cm ³ (Co)
• Solubility in water	Insoluble (WC)The water solubility of Co at 20°C = 2.94 mg/L
• Partition coefficient (n-octanol/water)	Not relevant as the substances are inorganic
• Auto-ignition temperature	Tungsten carbide is not a self-heating substance down to size of 0.53 µm
• Decomposition temperature	Greater than 2920 °C (WC melting point) 1494 °C (Co melting point)
• Viscosity	Not relevant due to physical form (powder)
• Explosive properties	Not explosive
• Oxidizing properties	Not oxidizing

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

- 10.1 Reactivity:** No hazardous reactions known.
- 10.2 Chemical stability:** Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
- 10.3 Possibility of hazardous reactions:** None known.
- 10.4 Conditions to avoid:** Avoid formation and accumulation of dust.
- 10.5 Incompatible materials:** None known.
- 10.6 Hazardous decomposition products:** PEG decomposes (100 - 250°C) into several substances, some of which are classified as reproductive toxicants (e.g. 2-methoxyethanol and 2-ethoxyethanol.)

11. TOXICOLOGICAL INFORMATION

Some toxicological information on the tungsten carbide and cobalt mixture is available. For endpoints where data is not available on the mixture, data on the individual components is included.

11.1 Information on toxicological effects:

Endpoint	Tungsten Carbide	Cobalt
Acute oral	Rat (male/female) LD ₅₀ reported to be >2000 mg/kg bw (OECD 401).	Rat (female) LD ₅₀ reported to be 550 mg/kg bw (OECD 425).
Acute inhalation	Rat (male/female) LC ₅₀ > 5.3 mg/L (OECD 403)	Fatal if inhaled. Rat (male/female) LC ₅₀ <0.05 mg/L (OECD 436)
	Studies conducted on Hardmetal (WC-Co): WC-10% Co, pegged: Rat (male/female) LC ₅₀ (4 hr) reported to be c. 0.8mg/L (OECD 403) WC-30% Co, waxed: Rat (male/female) LC ₅₀ (4 hr) reported to be <0.14 mg/L (US EPA OPPTS 870.1300). WC-10% Co, waxed: Rat (male/female) LC ₅₀ (4 hr) reported to be 0.4 mg/L (US EPA OPPTS 870.1300). WC-10% Co, waxed: Rat (male/female) LC ₅₀ (4 hr) reported to be >1 mg/L (US EPA OPPTS 870.1300). WC-6% Co, waxed: Rat (male/female) LC ₅₀ (4 hr) reported to be 0.75 mg/L (US EPA OPPTS 870.1300).	
Acute dermal	Rat (male/female) LD ₅₀ reported to be >2000 mg/kg bw (OECD 402).	Low acute toxicity: LD ₅₀ >2000 mg/kg.
Skin corrosion/irritation	In a skin irritation study conducted on rabbits (male), tungsten carbide elicited no dermal irritation (OECD 404).	Not classified: OECD TG 439: 95.1% (Non-irritant).
Eye damage/irritation	In an eye irritation study conducted on rabbits, tungsten carbide elicited no eye irritation (OECD 405).	An in vitro bovine corneal opacity and permeability study (OECD 437) on cobalt was not corrosive or severely irritating. Cobalt was irritating to the conjunctivae of rabbits in an acute eye irritation (OECD 405) study. Mean scores ranged between 1.33 and 2.33 with a maximum of 3; irritation was fully reversible within 7-days.

<p>Respiratory/skin sensitization</p>	<p>In a Guinea pig maximization test (OECD 406), tungsten carbide did not produce evidence of skin sensitization (delayed contact hypersensitivity) in any of the test animals.</p> <p>No respiratory sensitization study is available for tungsten carbide.</p>	<p>In the guinea pig maximization test (OECD 406) the reactivity at the test sites to repeated open application was dose and time dependent. In the general population retrospective study 8.7% of patients showed a positive reaction after patch testing with men 4.9% and women 10.5%.</p> <p>A case report of occupational exposure to cobalt resinate verified respiratory sensitivity of a worker to cobalt resinate and cobalt stearate by bronchio-provocation-testing with each substance. The worker did not respond to bronchio-provocation after the inhalation administration of cobalt tellate. The cobalt industry-wide questionnaire showed that there is industry experience with cobalt resinates and cases of occupational asthma. Based on available information, there is no indication the frequency of occupational asthma in workers is high.</p>
<p>Germ cell mutagenicity</p>	<p>The individual components of the mixture, tungsten carbide and cobalt are not mutagenic. However, <i>in vitro</i> mammalian alkaline elution and comet assays, as well as chromosomal aberration studies on the tungsten carbide and cobalt mixture resulted in positive mutagenic potential. Limited <i>in vivo comet assay</i> studies in rats were equivocal.</p>	
<p>Carcinogenicity</p>	<p>No indication of human carcinogenicity.</p>	<p>Exposure Route: Inhalation. Long term animal experiment (rat) (OECD 451). Presumed to have carcinogenic potential for humans; largely based on animal evidence.</p> <p>The mixture of WC+Co is classified by IARC as <i>probably carcinogenic to humans</i> (Group 2A) based on limited evidence for human for the carcinogenicity of Co metal with WC, and inadequate evidence in humans for the carcinogenicity of Co metal without WC).</p> <p>The US NTP considers cobalt-tungsten carbide (powders and hardmetals) as <i>reasonably anticipated to be a human carcinogen</i> based on limited evidence of carcinogenicity from human studies and supporting evidence from studies on mechanistic of carcinogenesis.</p> <p>Cobalt is "known to the state of California to cause cancer." (Proposition 65)</p>
<p>Reproductive toxicity</p>	<p>No reproductive/developmental studies are available for tungsten carbide. However, data are available on sodium tungstate and tungsten blue oxide, which are used for read across. Tungsten carbide is not considered a reproductive toxicant based on a one-generation reproductive study (EPA OPPTS 870.3800/870.3650) on sodium tungstate that resulted in no significant effects on reproductive/developmental parameters, as well as a lack of</p>	<p>Animal data on soluble cobalt compounds supports adverse effects on male reproductive organs (but no relevant data is available indicating adverse effects on female reproductive parameters) which has led to the classification of several cobalt substances for impairment of fertility. There is limited rodent developmental toxicity data on cobalt compounds.</p>

	reproductive organ effects in male and female rats following a 28 –days inhalation exposure (OECD 412) to tungsten blue oxide.	
STOT single exposure	The following clinical signs were observed in rats after a 4-hr exposure to 0.14 – 0.53 mg/L of tungsten carbide (88 or 94%) and cobalt (6 or 12%) mixtures (Health Effects Test Guidelines, OPPTS 870.1300): difficulty breathing, rapid breathing, unkempt appearance, feces few or absent, tremors, decreased activity, scabbed facial area, red discolored facial hair, red/brown material around the nose, and skin cold to touch, red vulva discharge, vocalization, and red material around the mouth. Body weights decreased after exposure and then increased through the end of the observation period. Surviving animals regained their pretest weight by the end of the 14-day observation period. At necropsy, red discoloration of the lungs was noted.	
STOT repeated exposure	Inhalation exposure to hardmetal can potentially lead to hardmetal disease characterized, in its most typical clinical presentation, by giant-cell interstitial pneumonia that can develop into pulmonary fibrosis. A study was conducted on a tungsten carbide and cobalt mixture in a ratio of 75:25 and was administered via inhalation for 35 days followed by a 20-day post exposure period. Following inhalation exposure, an acute inflammatory reaction later replaced by focal pneumonitis and residual bronchial epithelial hyperplasia and metaplasia were observed.	
Aspiration hazard	Tungsten carbide is not an expected aspiration hazard due to physical form.	Cobalt is not an expected aspiration hazard due to physical form.

Information on likely routes of exposure

The relevant routes of exposure for the general population are the oral, dermal, and inhalation routes. The most relevant routes of potential exposure to workers would be the dermal and inhalation routes.

Symptoms related to the physical, chemical and toxicological characteristics

In general, metal powders or dust may cause mechanical eye and skin irritation. Inhalation of powder or dust may cause mild respiratory tract irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Immediate effects from short term exposure: None known

Delayed effects from chronic exposure: Inhalation exposure can potentially lead to hard metal disease characterized, in its typical clinical presentation, by giant-cell interstitial pneumonia that can develop into pulmonary fibrosis.

Interactive effects

Hard metal toxicity is different than the individual constituents. Please refer to mutagenicity, carcinogenicity, and STOT repeated sections described above

12. ECOLOGICAL INFORMATION

No Eco toxicological information on the tungsten carbide and cobalt mixture is available. Data on the individual components or read-across substances are included. For some of the endpoints read across to sodium tungstate was conducted to represent tungsten carbide; whereas data for cobalt dichloride was used to represent cobalt metal.

12.1: Toxicity		
Endpoints	Tungsten Carbide	Cobalt
Toxicity to fish	Zebrafish 96-h LC ₅₀ >1000 mg tungsten carbide/L (OECD 203).	Rainbow Trout (freshwater) 96-h LC ₅₀ = 1.512 mg Co/ (ATSM)
	Zebrafish 38-day flow-through early-life stage/reproduction/ (sub) lethal effects NOEC ≥9.8 mg sodium tungstate/L (approximately 5.74 mg tungsten/L) (OECD 210).	Zebrafish (freshwater) EC ₁₀ = 351.4 mg Co/L. Sheepshead minnow (marine) EC ₁₀ = 31,802 mg Co/L. (OECD 210)

Toxicity to invertebrates	<p><i>Daphnia magna</i> 48-h EC₅₀ >1000 mg tungsten carbide/L (OECD 202).</p> <p><i>Daphnia magna</i> 21-day NOEC based on immobilization ≥85.1 mg sodium tungstate/L (approximately 50 mg tungsten/L) (OECD 211).</p> <p><i>Daphnia magna</i> 21-day NOEC based on reproduction and growth 44.2 mg sodium tungstate/L (approximately 26 mg tungsten/L) (OECD 211).</p>	<p><i>Ceriodaphnia dubia</i> (freshwater) LC₅₀ 0.61 mg cobalt/L (USEPA)</p> <p><i>Dendraster excentricus</i> (marine) LC₅₀ 2.32 mg cobalt/L (ASTM)</p> <p><i>Hyallela azteca</i> (freshwater) EC₁₀= 0.006 mg cobalt/L (OECD 211)</p> <p><i>Neanthes arenaceodentata</i> (marine) EC₁₀= 0.21 mg cobalt/L (ASTM)</p>
Toxicity to algae and plants	<p><i>Desmodesmus subspicatus</i> (algae) 72-h EC₅₀ based on growth rate >1 mg tungsten carbide/L (OECD 201).</p> <p><i>Pseudokirchneriella subcapitata</i> (algae) 72-h EC₅₀ based on growth rate >17.7 mg sodium tungstate/L (approximately 10.4 mg tungsten/L) (OECD 201).</p> <p><i>Pseudokirchneriella subcapitata</i> (algae) 72-h NOEC based on growth rate 0.81 mg sodium tungstate/L (approximately 0.476 mg tungsten/L) (OECD 201).</p>	<p><i>Pseudokirchnerella subcapitata</i> (freshwater) EC₅₀ based on growth rate 0.144 mg dissolved cobalt/L (OECD 201).</p> <p><i>Champia parvula</i> (marine) EC₅₀ based on cytoscarp production 0.024 mg dissolved cobalt/L (USEPA 821)</p> <p><i>Lemna minor</i> 7-day (freshwater) EC₁₀ based on growth rate 0.005 mg dissolved cobalt/L (OECD 211).</p> <p><i>Champia parvula</i> (marine) EC₁₀ based on cytoscarp production 0.001 mg dissolved cobalt/L (USEPA 821).</p>

12.2 Persistence and degradability: Although no data were available for the tungsten carbide and cobalt mixture, degradation and persistence are not a relevant pathway for this mixture as it is inorganic.

12.3 Bio accumulative potential: Bioaccumulation/bio concentration of tungsten carbide is not expected to occur in aquatic or sediment species. The bioavailability of tungstate (the most common bioavailable form) from tungsten compounds is expected to be at low concentrations in the water column due to stream and river sediment adsorption and low potential for leaching from soils. Furthermore, any uptake mediated by transport proteins would be expected to be internally regulated. The absence of methylated tungsten species also supports the claim that bioaccumulation is not expected to be of concern for tungsten carbide as an inorganic metal compound.

Based on BCFs calculated from paired concentrations of tungsten in soil and worm, or soil and plant tissue, tungsten carbide exposures are not expected to result in the bioaccumulation of tungsten in terrestrial organisms.

Cobalt has low potential for bioaccumulation based on the following bio concentration factors (BCF) and bioaccumulation factors (BCA):

- Aquatic plants: BCF: >100-5000.
- Aquatic invertebrates: BCF <300.
- Fresh water, Fish: BCF/BAF <10.
- Marine, Fish: BCF/BAF <10.

- 12.4 Mobility in soil:** No data on the behavior the tungsten carbide and cobalt mixture in the environment are available. However, data for sodium tungstate and tungsten metal are expected to adequately capture the range of mobility of tungsten carbide in the environment. The adsorption/desorption is highly dependent on the characteristics of the soil system in question. For example, soil sorption coefficients of tungsten metal and sodium tungstate are found to increase with decreasing pH. Additionally, soil-tungsten systems may take up to approximately 3-4 months to reach equilibrium. Soil sorption coefficients measured for sodium tungstate ranged from 16.6 to 863 L/kg. In addition, because of the low water solubility of cobalt, mobility of this metal in soil is negligible.
- 12.5 Results of PBT and vPvB assessment:** Tungsten carbide and cobalt are inorganic substances, and therefore the PBT and vPvB assessment is not required.
- 12.6 Other adverse effects:** None known

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose in accordance with local/regional/national/international regulations. Two options are recommended:

1. Re-use
2. Recycling or other recovery

If this product becomes waste, the waste is to be considered as hazardous waste. Wastewater should be processed through a sewage treatment plant (STP) either on-site or off-site.

14. TRANSPORT INFORMATION

- 14.1 UN-No.:** UN3077
- 14.2 UN proper shipping name:** Environmentally hazardous substance, solid, n.o.s (contains cobalt)
- 14.3 Transport hazard class(es):** 9
- 14.4 Packing group:** III
- 14.5 Environmental hazard(s):** Marine pollutant
- 14.6 Special precaution(s) for user:** A97, A158, A179 (IATA); 274, 335 (IMDG); 274(RID); 274, 335, 601(ADR); 274, 335, 601(ADN)
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations (USA)

Occupational Safety and Health Act (OSHA): Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA): Components of this product are listed on the TSCA inventory.

Superfund Amendments and Reauthorization Act (SARA): Cobalt is subject to the requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986.

State Regulatory Information: This product contains cobalt which is listed in California Proposition 65 as a known cancer-causing chemical.

15.2 Chemical safety assessment: Not applicable.

16. OTHER INFORMATION

Full text of classifications (GHS)	<p>Eye Irrit. 2B, H320 Repr. 2; H361f Acute Tox. 1, H330 Acute Tox. 3, H331 Acute Tox. 4, H302 Carc. 1B, H350i STOT RE 1, H372</p> <p>Resp. Sens. 1B, H334 Skin Sens.1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411</p>	<p>Eye Irritation, category 2B Reproductive Toxicity, category 2 Acute Toxicity, category 1 Acute Toxicity, category 3 Acute Toxicity, category 4 Carcinogenicity, category 1B Specific Target Organ Toxicity – Repeated exposure, category 1 Respiratory Sensitization, category 1B Skin Sensitization, category 1 Aquatic Toxicity (Acute), category 1 Aquatic Toxicity (Chronic), category 1 Aquatic Toxicity (Chronic), category 2</p>
Full text of abbreviated H statements	<p>H302 Harmful if swallowed H330 Fatal if inhaled H331 Toxic if inhaled H350i May cause cancer by inhalation H372 Causes damage to lungs through prolonged or repeated exposure by inhalation H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled H317 May cause an allergic skin reaction H320 Causes eye irritation H361f Suspected of damaging fertility H400 Very toxic to aquatic life H410 Very toxic to aquatic life with long lasting effects H411 Toxic to aquatic life with long lasting effects</p>	
Revision(s):	<p>Changes in the revised Safety Data Sheet: Safety Data Sheet revised to meet the new classification and other requirements of GHS. Section 3: minor changes</p> <p>SDS prepared on 30 June 2014. Prepared in accordance with 29 CFR 1910.1200.</p>	
References:	<p>Tungsten Carbide Chemical Safety Report. September, 2010. International Tungsten Industry Association. Cobalt Chemical Safety Report, July 2012, Cobalt Development Institute.</p>	

Abbreviations:

ACGIH	American Conference of Industrial Hygienists
Al	Aluminum
ASTM	American Society for Testing and Materials
BAF	Bioaccumulation Factors
BCF	Bio concentration Factors
bw	Body weight
°C	Degrees Celsius
Carc	Carcinogenicity
CAS	Chemical Abstracts Service
CEC	Cation Exchange Capacity
CFR	Code of Federal Regulations
CI	Confidence Interval
CLP	Classification, Labelling and Packaging
Cm	Centimeter(s)

Co	Cobalt
CO ₂	Carbon Dioxide
DNA	Deoxyribonucleic Acid
DNEL	Derived No Effect Level
e-SDS	Extended Safety Data Sheet
EC	European Commission
EC ₅₀	Effect Concentration 50%
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
EPA	Environmental Protection Agency
EPA OPPT	Environmental Protection Agency Office of Pollution Prevention and Toxics
EU	European Union
Fe	Iron
FSSS	Fisher Sub Sieve Sizer
g	Gram(s)
h	Hour(s)
IARC	International Agency for Research on Cancer
IBC	International Bulk Chemical
IRIS	Integrated Risk Information System
kg	Kilogram(s)
L	Liter(s)
LC ₅₀	Lethal Concentration 50%
LD ₅₀	Lethal Dose 50%
LOAEC	Lowest Observable Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
m ³	Cubic Meter(s)
m	Meter(s)
MARPOL	International Convention for the Prevention of Pollution from Ships mg Milligram(s)
Mn	Manganese
MS	Member State
ng	nanogram
Ni	Nickel
NIOSH	National Institute for Occupational Safety and Health
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
No.	Number
NTP	National Toxicology Program
OECD	Organization for Economic Co-operation and Development
OEL	Occupational Exposure Level
OSHA	Occupational Safety and Health Administration
PBT	Persistent, Bio accumulative, and Toxic
PNEC	Predicted No Effect Concentration
RCR	Risk Characterization Ratio
REACH	Registration, Evaluation, Authorization and Restriction of Chemical substances
Resp.	Respiratory
SDS	Safety Data Sheet
Sens.	Sensitization
SMR	Standard Mortality Ratio
spERC	Specific Emission Release Categories
STOT-RE	Specific Target Organ Toxicity - Repeat
STP	Sewage Treatment Plant
TLV	Threshold Limit Value
µg	Microgram(s)
µm	Micrometer(s)
UN	United Nations
USEPA	United States Environmental Protection Agency
vPvB	very Persistent, very Bio accumulative
W	Tungsten
WC	Tungsten carbide

Users Responsibilities

This SDS provides information consistent with recommended applications of these products and anticipated activities involving the product. It is the user's responsibility to identify and protect against health and safety hazards presented by modification of hard metal powders and products after manufacture. Individuals handling hard metal powders should be informed of all relevant hazards and recommended safety precautions, and should have access to the information contained in this SDS.

Disclaimer

The information contained herein is based upon data provided by manufacturers and suppliers of raw materials used in the manufacture of hard metal powders. The information is offered in good faith as accurate and correct, but no representations, guarantees, or warranties of any kind are made as to its accuracy or completeness, suitability for particular applications, hazards connected with the use of the hard metal blanks, or the results to be obtained from the use thereof. The user assumes all risk and liability of any use or handling of any material beyond Robbjacks control. Variations in methods, conditions, equipment used to store, handle, or process the material, and hazards connected with the use of the hard metal blanks are solely the responsibility of the user and remain at its sole discretion. This SDS is intended to be used solely for the purpose of satisfying informational requests made pursuant to Title 29 of the Code of Federal Regulations, Section 1910.1200 *et seq.* It is not intended to pre-empt, replace, or expand the terms contained in the Robbjack Conditions of Sale. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user, and the user has the responsibility to provide a safe workplace, to examine all aspects of its operation, and to determine if or where precautions, in addition to those described herein, are required. This information may not be valid for special products when manufactured with alternate materials meeting the special requirements of a particular user.

ROBBJACK MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

End of Safety Data Sheet_